



Hardware

Size	298mm x 206mm x 43mm (11.7in x 8.1in x 1.7in)
Weight	1.6 kg (3.5 lb) with Standard Battery 1.8 kg (4.0 lb) with Extended Battery
Memory	8 GB
Expandable memory	No
Processor	Intel BayTrail-I Atom E3826 1.46GHz dual-core
Wireless	Wi-Fi (802.11 a/b/g/n)
Power	Standard Battery Pack: 10.8V, 4.5mAh, 49Whr/5 hour Extended Battery Pack: 10.8V, 9.1mAh, 98Whr/10 hour

Environmental

Temperature – Operating	-30 °C to +55 °C (-22 °F to +130 °F), MIL-STD-810G Method 502.5, Procedure II & III (Low Temp Operating)
Temperature – Storage	-40 °C to +70 °C (-40 °F to +158 °F), MIL-STD-810G Method 502.5, Procedure I (Low Temp. Storage), MIL-STD-810G Method 501.5, Procedure I (High Temp. Storage)
Humidity	90% RH, MIL-STD-810G Method 507.5, Procedure II (Humidity Aggravated Cycle)
Sand and dust	IP65, IEC 60529 (Protected against dust, survives driving rain and water spray from any direction)
Water	IP65, IEC 60529 (Protected against dust, survives driving rain and water spray from any direction)
Drops	Survives multiple 1.22 m (4 ft) drops, MIL-STD-810G Method 516.6 Procedure IV, Transit Drop
Vibration	Vibration: General minimum integrity and loose cargo tests, MIL-STD-810G, Method 514.6, Procedure I Procedure II, Category 5 (Vibration) (Vibration); Truck/Trailer-Loose Cargo Annex C, figure 514.6C-4, Table 514.6C-1, one hour)
Altitude	Operational at 4,572 m (15,000 ft), MIL-STD-810G, Method 500.5, (Altitude) Procedure I, II & III

Interface

Display – General	10.1 inch full color sunlight readable display with Corning® Gorilla® Glass Panel and multi-touch capacitive touchscreen
Display – Resolution	WUXGA (1920 x 1200)
Keyboard	4 programmable function buttons, OK button, and Windows button
Audio	Internal mono speaker and microphone, 3.5 mm audio jack
Operating system	Microsoft Windows 10 Professional

Input/Output

Ports:	
RS-232 9-pin	Yes, 9 pin male
USB client	No
USB host	Yes (2)
Bluetooth wireless technology	Yes, Bluetooth 4.0
DC Power	Yes. 19 VDC via docking station, AC adapter or Vehicle adapter
Expansion	
Type I CF slot	No
Type II CF slot	No
ExpressCard (34mm) slot for cell modem	No
SD slot	No
Micro SD slot	No

Other

Office Dock
Active Vehicle Dock

Yes
Yes, the ruggedized Active Vehicle Mount for Marine & Supervisor applications can power the Tablet and adds additional ports

Integrated GPS
Front facing camera
User facing camera
Integrated 3.75G cellular modem
Accelerometer
Digital Compass
Integrated Scanner
VOIP Support
Cell Phone
Warranty
WWAN Modules

Yes, 2-4m (6-13 ft)
Yes, 8MP camera with LED flash for photos and videos
No
4G LTE WWAN
Yes
Yes
No
Yes, requires 3rd-party app such as Skype
Data only with micro SIM card
2-year standard warranty, extendable up to 5 years
Americas: 4G: LTE-FDD, HSPA+, GSM/GPRS/EDGE
(Frequency bands B1, B2, B4, B5, B8, B13, B17, B25, BC0, BC1, BC10)

EMEA, Australia, New Zealand: 4G: LTE-FDD, HSPA+, GSM/GPRS/EDGE
(Frequency bands B1, B2, B3, B5, B7, B8, B20)

2.4 GHz Radio Modem

Standard, a 2.4GHz radio for Robotic applications is available which can be mounted on the back

Specifications subject to change without notice.

© 2016, Trimble. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble registered in the United States and in other countries. Trimble Tablet 10 is a trademark of Trimble. Microsoft, Windows, Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. All other brand names and trademarks are property of their owners. Color display images shown may vary slightly from actual display. (11/16)

Trimble Heavy Civil Construction Division

10368 Westmoor Drive
Westminster, Colorado 80021
USA
800-361-1249 (Toll Free)
+1-937-245-5154 Phone
+1-937-233-9441 Fax
www.trimble.com

Trimble Authorized Distribution Partner